


REMARKS

Amendments to the specification have been made and are submitted herewith in the attached Substitute Specification. A clean copy of the specification and a marked-up version showing the changes made are attached herewith. The claims have been amended in the attached Preliminary Amendment. All amendments have been made to place the application in proper U.S. format and to conform with proper grammatical and idiomatic English. None of the amendments herein are made for reasons related to patentability. No new matter has been added.

In the event the U.S. Patent and Trademark Office determines that an extension and/or other relief is required, applicant petitions for any required relief including extensions of time and authorizes the Commissioner to charge the cost of such petitions and/or other fees due in connection with the filing of this document to **Deposit Account No. 03-1952** referencing docket no. **449122081300**. However, the Commissioner is not authorized to charge the cost of the issue fee to the Deposit Account.

Dated: May 13, 2005

Respectfully submitted,



By
Kevin R. Spivak
Registration No.: 43,148
MORRISON & FOERSTER LLP
1650 Tysons Boulevard
McLean, Virginia
(703) 760-7762 - Telephone
(703) 760-7777 - Facsimile

Description

Contact piece having rounded-off slot edges

5 CLAIM FOR PRIORITY

This application is a national stage of PCT/DE2003/003461, published in the German language on October 13, 2003, which was filed in the english language on November 15, 2002.

10

TECHNICAL FIELD OF THE INVENTION

The invention relates to a contact piece of a contact arrangement, and in particular, for ~~the purpose of interrupting a current in a distribution system having a contact carrier~~ which has a hollow cylindrical wall section and a base wall and having a contact disk which lies opposite the base wall in a longitudinal direction, slots being provided for the purpose of producing a magnetic field.

20 BACKGROUND OF THE INVENTION

In the conventional art, ~~such~~ a contact piece is known, for example, from DE 34 15 743 A1. Therein, a contact arrangement is shown for a vacuum interrupter. The contact arrangement has a stationary contact piece and a movable contact piece which is guided such that it can move in relation to ~~said the~~ stationary contact piece, ~~said the~~ contact pieces lying with their end faces opposite one another in the axial direction. The contact pieces each comprise a pot-shaped contact carrier, which has a hollow-cylindrical wall section and a base wall, and a contact disk which lies axially opposite the base wall. In order to produce an axial magnetic field, slots are provided in the base wall, the wall section and in the contact disk, and these slots delimit conductor tracks which extend helically, with the result that an azimuthal component is impressed on a current flowing via the contact piece and an axial magnetic field is produced. The contact piece designed in this way is envisaged for installation in a vacuum-operated power breaker which is

~~2002P18239WOUS/
PCT/DE2003/003461~~

- 2 -

provided for the purpose of interrupting the current flow in an energy distribution system, for example in the event of a short circuit.

By separating the contact pieces of the contact arrangement of the vacuum-operated power breaker, an arc is drawn between the contacts. The magnetic field produced by the slots counteracts a self-contraction of the arc and contributes to quenching of the arc. Owing to the slots provided in the contact disk, the occurrence of eddy currents in the contact disk is also suppressed. The slots are generally produced by metal-cutting manufacturing techniques such as milling, lathe work, drilling and are mechanically and/or electrochemically burred.

The previously known contact piece has the disadvantage that sharp edges are formed at the rims of the slots when said slots are introduced, and these sharp edges increase the electric field strengths, which are in any case very high in the contact region, by a factor β which may be between 3 and even over 10, depending on the radius of curvature of the edges and the contact spacing. However, high electric field strengths in the contact region have a disadvantageous effect on the dielectric strength of contact arrangements which are fitted with such contact pieces.

SUMMARY OF THE INVENTION

~~It is the object of the invention to provide~~ The invention provides a contact piece of the type mentioned initially which prevents high electric field strengths in the contact region of contact arrangements.

The invention achieves this object by the rims of the slots having rounded-off edges having a defined radius.

In accordance with one embodiment of the invention, the dielectric strength of a contact piece can firstly be influenced in a targeted manner. ~~Whilst~~ While the mechanical or electrochemical burring of previously known contact pieces leads to slot rims having edges whose curvature is more or less arbitrary, the rims of slots according to the invention have edges having a defined radius. In the process, the radius remains constant according to the invention over the entire

extent of the slots so as to prevent local fluctuations in the dielectric strength in the case of contact arrangements having contact pieces according to the invention. The defined radii may be produced, for example, with the aid of a radius milling
5 cutter which has been developed for this purpose, and thus mechanically. For this purpose, the radius milling cutter is passed through the entire slot. In addition, it is possible for the defined curvatures of the edges to be designed by means of numerically controlled machine tools and appropriately shaped
10 milling heads. In the case of composite materials, for example comprising copper and chromium, it is also possible for the defined curvatures to be produced by means of powder metallurgy using the shaped part technique or by means of cold reforming, i.e. by means of embossing.

15 The radius R is advantageously set as a function of the voltage of the distribution system U in accordance with the rule on dimensions:

$$R \geq 2 \cdot 10^{-4} \cdot U^2 + 8.5 \cdot 10^{-3} \cdot U + 0.34,$$

20 where U has the unit kilovolts and R has the unit millimeters. If these minimum values which are dependent on the voltage are adhered to, the contact piece has a particularly high dielectric strength.

25 The slots advantageously have slot ends in the form of a rounded hole. In this advantageous development of the invention, the production of the rounded-off edges having a defined radius is simplified further since the curvatures required in the end region of the slots which is difficult for
30 machine tools to gain access to can be formed by simply drilling or circular milling.

In accordance with one development in this regard, the diameter of the rounded hole is in the region of a slot width of the
35 slots. This setting of the dimensions further simplifies production of the edges with their defined curvatures in the end region of the slots.

- As an alternative to this, the slots have rectangular slot ends. The production of this embodiment of the invention is made more difficult owing to the rectangular slot end formation. However, as little material as possible is removed from the contact piece by rounding off the edges of the rims, as a result of which the conductivity, the heat exchange and the robustness of the contact piece are improved.
- 10 The slots are advantageously provided in the wall section and are inclined with respect to the longitudinal direction. In this way, a coil former is produced which favors quenching of the arc.
- 15 In accordance with one advantageous development, the slots are formed in the contact disk. The provision of the slots in the contact disk prevents, for example, disadvantageous eddy currents in the contact disk. According to the invention, the slots may be provided exclusively in the contact disk or else
- 20 both in the wall section and in the contact disk.

The slots in the contact disk are advantageously curved, in which case they follow the profile of the slots in the coil former. This increases the size of the azimuthal component of the current flowing via the contact piece and intensifies the magnetic field produced.

25

In addition, it may be advantageous if the slots are provided in the base wall. The slots in the base wall are advantageously curved such that an azimuthal component is impressed on the current as early as its flow via the base wall of the contact carrier. In this case, the slots in the coil former continue on from the slots in the base wall. In the context of the invention it is naturally also possible for the base plate, the coil former and also the contact disk to have slots.

30

35

BRIEF DESCRIPTION OF THE DRAWINGS

~~Further expedient refinements and advantages of the invention~~
~~are the subject matter of the description~~
is described in more
detail below of using exemplary embodiments of the invention
with reference to the figures ~~of in the drawings~~, in which
5 corresponding components are provided with the same reference
numerals and in which:

10 ~~Figure 1~~ shows an exemplary embodiment of a contact disk of
the contact piece according to the invention, ~~and~~.

~~Figure 2~~ shows an exemplary embodiment of a contact carrier of
the contact piece according to the invention.

DETAILED DESCRIPTION OF THE INVENTION

15 Figure 1 shows an exemplary embodiment of a contact disk 1 of
the contact piece according to the invention. The contact disk
1 shown has a circular outer contour. Slots 2 are introduced
into the contact disk 1 from the outside. The slots do not
extend in the form of a star from the outside towards the
20 center of the circular contact disk 1 but are formed such that
they are at a slight angle with respect to the star-shaped
profile, as a result of which an azimuthal component is
impressed on a current flowing via the contact disk towards the
center. In addition, the slots 2 serve the purpose of
25 suppressing eddy currents.

The slots 2 are delimited by rims which have rounded-off edges
3. The radius of the edge curvature in the exemplary embodiment
shown is 0.5 mm. Such a contact disk is therefore preferably
30 suitable for use in distribution systems having an operating
voltage of up to 27 kV, as results from the abovementioned rule
on dimensions.

The edges 3 of the rims of the slots 2 are themselves rounded-
35 off in the end regions of the slots 2, or in other words at the
slot end 4, and have a constant radius of curvature over the
entire slot profile. In the exemplary embodiment shown,

however, different slot ends 4 are illustrated. The slot end which is given the reference numeral 5 is shaped in the form of a hole, whose radius essentially corresponds to the diameter of the slot 2. The slot end having the reference numeral 6 is likewise in the form of a hole, but the diameter of the hole essentially corresponds to the diameter of the slot 2.

The reference numeral 7 denotes rectangular slot ends, whose rims or limits have, however, rounded-off edges having a constant radius, as do the holes.

Figure 2 shows an exemplary embodiment of a contact carrier 8 of a contact piece according to the invention which has a wall section 9 and a base wall 10. A fixing section 11 can also be seen in the base wall 10, and this fixing section 11 can be connected to a current-carrying contact bolt (not shown) at a fixing recess 12. As is the case with the contact disk 2, slots 2 are provided in the wall section 9 which have rims having edges 3. The rims of the slots 2 are rounded-off in their end regions or in other words at the slot ends 4, the slot ends 6 having the shape of a hole, whose diameter essentially corresponds to the diameter of the slot 2. As a deviation from this, the rim of a slot end 7 is rectangular.

The base wall 10 does not have any slots 2 in the exemplary embodiment illustrated.

The contact carrier is generally produced from a highly conductive material, such as copper. The contact disk 1 is advantageously made of a composite material and in particular of a copper/chromium alloy.

2002P18239WOUS/
PCT/DE2003/003461

- 8 -

7.1.2003

~~Patent-claims~~ What is claimed is: